

**■ HCMOS VCXO 6PAD 5.0x3.2**



- Miniature Ceramic Surface Mount package
- Wide pulling range and Low phase noise
- Fundamental crystal design

- Applications : Telecommunications, Network equipment

**■ Standard Specification**

Frequency range	4MHz to 54MHz	1MHz to 170MHz	1MHz to 100MHz
Supply voltage	1.8V to 2.5V	3.3V	5.0V
Pin1 Control Voltage	1.25V±1.05V(2.5V)	1.65V±1.35V	2.5V±2.0V
Frequency Pull Range	±50ppm Min or please specify		
Linearity	10% Max		
Frequency slope	Positive		
Current consumption	35mA Max or please specify		
Frequency Stability	±25ppm, ±50ppm, ±100ppm		
Operating Temperature Range	-20 to 70°C, -40 to 85°C		
Storage Temperature Range	-55 to 125°C		
Output load condition	CMOS 15pF		
Symmetry (Duty)	50% ±10%		
Output rise and fall time ( Tr /Tf )	10ns Max		
Output high level	90% Vdd Min		
Output low level	10% Vdd Max		
Pin 2/5 Function	Enable input voltage	70% Vdd Min or N.C	
	Disable input voltage	30% Vdd Max	
Oscillation start up time	5ms Max		
Aging (Initial first year)	± 3ppm Max		
Phase jitter (12KHz ~ 20MHz)	1.0ps RMS Max or please specify		
Period jitter (pk-pk)	25ps Max		
Modulation band width	15KHz Min (at - 3dB)		

**■ Dimensions (mm)**



- CONNECTION**
- #1 V.C
  - #2 Tri-State or N.C
  - #3 GND
  - #4 OUTPUT
  - #5 Tri-State or N.C
  - #6 Vdd

**• Recommended Soldering Pattern**

